Strong Wind Protection

Severe Hail Protection

Heavy Snow Protection


Superior Fire Protection

Vertex N

TOPCon

Shield

TSM-NED19RC.20
600-625W



Key Features

Pass IEC 55mm diameter hail certificate at a speed of 33.9m/s
Effectively reduce over 50% probability of losses caused by hail damage*

Mechanical load with fixed mounting installation: +7000/-5000Pa
Mechanical load with tracking installation: +3600/-3000Pa

Pass IEC 61730-2 Class A+A fire rating certificate
Pass EN13501-1 Class B certificate (FIGRA 19W/s)
Pass UL61730 Type 30 fire resistance certificate

Uneven snow load capacity up to 6600Pa

*Please get in contact with Trina Solar technical team for more details on the VDE PRE/PML/AAL report.

Better bankability, more profit

- Highly reliable products reduce insurance costs and reduce payout risk
- High power up to 625W and 23.1% module efficiency, on 210 innovation platform
- Low voltage design with higher string power, effectively reducing BOS and LCOE
- High Bifaciality & excellent low-irradiation performance, improve electricity generation per Watt


High reliability, resist for extremes

- Pass salt, ammonia, dust, PID, LID, LeTID certificate

Diversified scenarios adaption

- Support diversified installation methods, suitable for various application scenarios
- Typical module format design, better compatibility with trackers
- Excellent compatibility with existing mainstream inverters

Performance Warranty



* Please refer to product warranty for details

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716/UL61730
ISO 9001: Quality Management System
ISO 14001: Environmental Management System
ISO45001: Occupational Health and Safety Management System

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© 2026 Trina Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
The right of final interpretation belongs to Trina Solar Co.,Ltd.
Version number: TSM_NA_EN_2026_A

Trinasolar

Vertex N

N-type TOPCon BIFACIAL DUAL GLASS MONOCRYSTALLINE MODULE

ELECTRICAL DATA (STC & NOCT)

Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Peak Power Watts-PMAX(Wp)*	600	458	605	462	610	465	615	469	620	473	625	477
Power Selection (W)**	0 ~ +5											
Maximum Power Voltage-VMPP (V)	39.43	37.30	39.57	37.40	39.79	37.60	39.97	37.80	40.24	37.90	40.46	38.10
Maximum Power Current-IMPP (A)	15.22	12.29	15.29	12.33	15.33	12.38	15.39	12.43	15.41	12.47	15.45	12.52
Open Circuit Voltage-VOC (V)	47.69	45.30	47.89	45.50	48.09	45.70	48.29	45.90	48.50	46.10	48.70	46.30
Short Circuit Current-ISC (A)	16.02	12.91	16.08	12.96	16.14	13.00	16.20	13.05	16.26	13.10	16.32	13.15
Module Efficiency η m (%)	22.2		22.4		22.6		22.8		23.0		23.1	

STC: Irradiance 1000W/m2, Cell Temperature 25°C, Air Mass AM1.5. NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s. *Measuring tolerance: ±3%. **Power selection up to: +3%.

Electrical characteristics with different power bin (reference to 5% & 10% backside power gain)

Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Peak Power Watts-PMAX(Wp)	630	660	635	666	641	671	646	677	651	682	656	688
Maximum Power Voltage-VMPP (V)	39.43	39.43	39.57	39.57	39.79	39.79	39.97	39.97	40.24	40.24	40.46	40.46
Maximum Power Current-IMPP (A)	15.98	16.74	16.05	16.82	16.10	16.86	16.16	16.93	16.18	16.95	16.22	17.00
Open Circuit Voltage-VOC (V)	47.69	47.69	47.89	47.89	48.09	48.09	48.29	48.29	48.50	48.50	48.70	48.70
Short Circuit Current-ISC (A)	16.82	17.62	16.88	17.69	16.95	17.75	17.01	17.82	17.07	17.89	17.14	17.95

Power Bifaciality:80±5%.

TEMPERATURE RATINGS


NOCT (Nominal Operating Cell Temperature)	43℃ (±2℃)
Temperature Coefficient of PMAX	- 0.29% /℃
Temperature Coefficient of VOC	- 0.24% /℃
Temperature Coefficient of ISC	0.04% /℃


Due to different testing methods, the actual performances might differ from the declared specifications.

APPLICATION CONDITIONS

Operating Temperature	-40~+85℃
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating	35A

CURVES OF PV MODULE






MECHANICAL DATA

Solar Cells	N-type TOPCon Monocrystalline
No. of cells	132 cells
Module Dimensions	2382×1134×30 mm (93.78×44.65×1.18 inches)
Weight	39.7 kg (87.5 lb)
Front Glass	AR Coating Heat Strengthened Glass
Back Glass	Heat Strengthened Glass
Frame	30mm(1.18 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm² (0.006 inches²) Portrait: 200/320 mm(7.87/12.60 inches) Length can be customized
Connector	TS4 Plus / TS4 / MC4 EVO2*
Fire Type	Type 30 or Class A
Packaging	Modules per box: 36 pieces Modules per 40'/53' container: 432 pieces

*The connector names listed are general names; specific types are subject to the certification documents.



CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© 2026 Trina Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
The right of final interpretation belongs to Trina Solar Co.,Ltd.

Version number: TSM_NA_EN_2026_A

www.trinasolar.com

Trinasolar