



Certificate of Compliance

Certificate: 80011826

Master Contract: 248189

Project: 80277995

Date Issued: 2026-01-15

Issued To: Trina Solar Co., Ltd.
No. 2 Tian he Rd
Trina PV Industrial Park
New District
Changzhou, Jiangsu, 213031
China

Attention: Zhangang Zhao

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.



Issued by: *Xiaoliang Gu*
Xiaoliang Gu

PRODUCTS

CLASS - C531110 - POWER SUPPLIES Photovoltaic Modules and Panels

CLASS - C531190 - POWER SUPPLIES Photovoltaic Modules and Panels - Certified to US Standards

Dual glass photovoltaic modules with maximum system voltage of 1500 V dc, Safety Class II PV modules, application Class A.

Model series:

TSM-xxxDEG15H(II) (xxx = 380 to 425 W), TSM-xxxDEG15H.20(II) (xxx = 380 to 425 W)

TSM-xxxDEG6H(II) (xxx = 310 to 355), TSM-xxxDEG6H.20(II) (xxx = 310 to 355)

TSM-xxxDEG15M(II) (xxx = 350 to 430), TSM-xxxDEG15M.20(II) (xxx = 350 to 430)

TSM-xxxDEG6M(II) (xxx=295 to 360), TSM-xxxDEG6M.20(II) (xxx=295 to 360)

TSM-xxxDEG15HC(II) (xxx= 350 to 420), TSM-xxxDEG15HC.20(II) (xxx= 350 to 420)



Certificate: 80011826

Master Contract: 248189

Project: 80277995

Date Issued: 2026-01-15

TSM-xxxDEG6HC(II) (xxx=295 to 335), TSM-xxxDEG6HC.20(II) (xxx=295 to 350)
 TSM-xxxDEG15MC(II) (xxx=350 to 425), TSM-xxxDEG15MC.20(II) (xxx=350 to 425)
 TSM-xxxDEG6MC(II) (xxx=295 to 345), TSM-xxxDEG6MC.20(II) (xxx=295 to 355)
 TSM-xxxPEG15H (xxx=335 to 375), TSM-xxxPEG15H.20 (xxx=335 to 375)
 TSM-xxxPEG6H (xxx=280 to 310), TSM-xxxPEG6H.20 (xxx=280 to 310)
 TSM-xxxDEG18MC.20(II) (xxx = 460 to 510), TSM-xxxDEG18M.20(II) (xxx = 465 to 510)
 TSM-xxxDEG19C.20 (xxx = 520 to 560), TSM-xxxDEG20C.20 (xxx = 570 to 610)
 TSM-xxxDEG15VC.20(II) (xxx= 465 to 490), TSM-xxxDEG21C.20 (xxx= 635 to 675)
 TSM-xxxNEG19RC.20 (xxx=525 to 650), TSM-xxxNEG19RC.27 (xxx=525 to 650),
 TSM-xxxNEG9RC.27 (xxx=375 to 445), TSM-xxxNEG21C.20 (xxx=635 to 725),
 TSM-xxxNEG20C.20 (xxx=580 to 655), TSM-xxxNED19RC.20 (xxx=525 to 650).
 TSM-xxxNEG21C.22 (xxx=635 to 725), TSM-xxxNEG21C.60 (xxx=635 to 725),
 TSM-xxxDEG21C.60 (xxx= 635 to 675), TSM-xxxNEG9RH.25 (xxx=415 to 460).

Note:

1. All electrical data are shown as relative to standard test conditions (STC) (1 000 W/m², (25 ± 2) °C, AM 1,5 according to IEC 60904-3).
2. The operating ambient temperature of these devices may exceed 40°C at full load for all wire sizes if it is determined suitable in the field use application.
3. Module Fire Performance in UL 61730
 Modules with metal frame: Type 30 or Type 29 or Type 38.

APPLICABLE REQUIREMENTS

CSA-C22.2 No. 61730-1:19 2 nd Edition	Photovoltaic (PV) module safety qualification – Part 1: Requirements for construction, 2019-12
CSA-C22.2 No. 61730-2:19 2 nd Edition	Photovoltaic (PV) module safety qualification – Part 2: Requirements for testing, 2019-12
UL 61730-1 2 nd Edition	Photovoltaic (PV) Module Safety Qualification – Part 1: Requirements for Construction, October 28, 2022
UL 61730-2 2 nd Edition	Photovoltaic (PV) Module Safety Qualification – Part 2: Requirements for Testing - second edition, 2022-10-28, reprint with revisions through and including November 10, 2023.

Notes:

Products certified under Class C531110 have been certified under CSA’s ISO/IEC 17065 accreditation with the Standards Council of Canada (SCC). www.scc.ca

