

N-type i-TOPCon Ultra

DUAL GLASS MONOCRYSTALLINE MODULE

TSM-xxxNEG9RP.25Z 460-480W

480W MAXIMUM POWER OUTPUT

24.0% MAXIMUM EFFICIENCY



Premium full black aesthetic

- Uniform, all-black, full-screen high density interconnection for a seamless design with no cell gaps



High power & efficiency

- Up to 480 W and 24% efficiency with low-voltage, high-current architecture for more power on limited roof space



Optimised performance


- Lower temperature coefficient and strong low-irradiance performance maximises power generation on rooftops



Long-term value for residential homes

- Low annual degradation backed by up to 30 year power warranty and 25 year product warranty
- Mechanical performance up to 5400 Pa static test load, Front and 3600 Pa static test load, Back
- Fire class rating C, Safety Class II

Performance Warranty



(*Please refer to Limited Warranty Supplement that applies to the TSM-***NEG9RP.25Z. Products installed within Australia & New Zealand market.)

Comprehensive Products and System Certificates

IEC61215/IEC61730

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO14064: Greenhouse Gases Emissions Verification

ISO45001: Occupational Health and Safety Management System



ELECTRICAL DATA (STC) TSM-xxxNEG9RP.25Z (xxx=460-480)

Peak Power Watts- $P_{MAX}(W_p)^*$	460	465	470	475	480
Power Selection (W)	0 ~ +5				
Maximum Power Voltage- $V_{MPP}(V)$	30.90	31.20	31.50	31.80	32.00
Maximum Power Current- $I_{MPP}(A)$	14.89	14.91	14.93	14.96	15.00
Open Circuit Voltage- $V_{oc}(V)$	36.90	37.10	37.30	37.50	37.70
Short Circuit Current- $I_{sc}(A)$	15.93	15.96	15.99	16.02	16.05
Module Efficiency $\eta_m(\%)$	23.0	23.3	23.5	23.8	24.0

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: $P_{max} \pm 3\%$, $V_{oc} \pm 3\%$ and $I_{sc} \pm 4\%$

ELECTRICAL DATA (NOCT)

Peak Power Watts- $P_{MAX}(W_p)$	349	353	357	361	364
Maximum Power Voltage- $V_{MPP}(V)$	29.00	29.20	29.40	29.60	29.80
Maximum Power Current- $I_{MPP}(A)$	12.06	12.11	12.16	12.20	12.23
Open Circuit Voltage- $V_{oc}(V)$	35.00	35.20	35.40	35.60	35.80
Short Circuit Current- $I_{sc}(A)$	12.80	12.83	12.85	12.88	12.90

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature) 43°C ($\pm 2^\circ\text{C}$)

Temperature Coefficient of P_{MAX} - 0.26% /°C

Temperature Coefficient of V_{oc} - 0.24% /°C

Temperature Coefficient of I_{sc} 0.04% /°C

Due to different testing methods, the actual performances might differ from the declared specifications.

APPLICATION CONDITIONS

Operating Temperature* -40~+70°C


Maximum System Voltage 1500V DC (IEC)

Max Series Fuse Rating 30A


*PV module 98th percentile operating temperature : 70°C

CURVES OF PV MODULE

I-V CURVES OF PV MODULE (475W)




P-V CURVES OF PV MODULE (475W)



MECHANICAL DATA

Solar Cells	N-type i-TOPCon Monocrystalline
No. of cells	150 cells
Module Dimensions	1762×1134×30 mm (69.37×44.65×1.18 inches)
Weight	21.1 kg (46.52lb)
Front Glass	1.6mm (0.06inches), AR Coating Heat Strengthened Glass
Back Glass	1.6mm (0.06inches), Heat Strengthened Glass
Frame	30mm (1.18 inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 6.0mm ² (0.009inches ²) Landscape :1100/1100 mm (43.31/43.31 inches)
Connector	Trinasolar, TS4-cd Stäubli Electrical Connectors AG PV-KST4-EVO2/xy_UR; PV-KBT4-EVO2/xy_UR PV-KST4-EVO2A/xy; PV-KBT4-EVO2A/xy
Packaging	Modules per box: 36 pieces Modules per 40' container: 936pieces



www.trinasolar.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© 2026 Trina Solar Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
The right of final interpretation belongs to Trina Solar Co., Ltd.
Version number: TSM_AUS_EN_2026_A
Country of Origin: China